IN THE CLAIMS

Please amend the claims as follows:

- 1. (Original) A method, comprising:
 - forming a safety sign, including forming an EL lighting surface into a chosen pattern; attaching the safety sign to one or more vehicles; and
- driving the vehicles in a formation on the road wherein the safety signs are visible to provide guidance for the vehicles.
- 2. (Original) A method, comprising:

forming a safety sign, including:

selecting a pattern to convey a visual safety message;

attaching the pattern to an EL lighting surface;

attaching the safety sign to one or more vehicles; and

driving the vehicles in a formation on a road wherein the safety signs are visible to provide guidance for the vehicles.

- 3. (Original) The method of claim 2, wherein the vehicles include snow plows.
- 4. (Original) The method of claim 2, wherein selecting a pattern to convey a visual safety message includes selecting a text message.
- 5. (Original) The method of claim 2, wherein attaching the pattern to an EL lighting surface includes attaching the pattern to an EL lighting surface with a yellow color when the EL lighting surface is illuminated.
- 6. (Original) The method of claim 2, wherein attaching the pattern to an EL lighting surface includes attaching the pattern to a substantially flat EL lighting surface dimensioned to comply with safety sign regulations.

Title: HIGH VISIBILITY SAFETY SIGN

- 7. (Original) The method of claim 6, wherein attaching the pattern to an EL lighting surface includes attaching the pattern to a substantially flat EL lighting surface of approximate rectangular dimensions of 72 inches wide and 8.5 inches tall.
- 8. (Original) A method, comprising:

forming one or more safety signs wherein each safety sign, includes:

selecting a pattern to convey a visual safety message;

attaching the pattern to an EL lighting surface;

attaching the safety sign to a transportation vehicle carrying an oversized load; and driving the vehicle on a road wherein the safety sign is visible to provide warning of the oversized load.

- 9. (Original) The method of claim 8, wherein the safety sign is attached to the front of the transportation vehicle.
- 10. (Original) The method of claim 8, wherein the safety sign is attached to the rear of the transportation vehicle.
- 11. (Original) The method of claim 8 wherein at least one safety sign is attached to at least one mud guard.
- 12. (Original) A safety sign, comprising:

a pattern selected to convey a visual safety message, the pattern being positionable on a rigid or flexible surface;

an EL lighting surface that contrasts the pattern, allowing the pattern to be seen from a distance; and

a power source coupled to the EL lighting surface.

13. (Original) The safety sign of claim 12, wherein the pattern includes a text message. Serial Number: 10/645,873 Filing Date: August 21, 2003

Title: HIGH VISIBILITY SAFETY SIGN

- 14. (Original) The safety sign of claim 12, wherein the pattern includes a triangle.
- 15. (Original) The safety sign of claim 12, wherein the pattern is layered over the EL lighting surface to mask a portion of the EL lighting surface to provide contrast.
- 16. (Original) The safety sign of claim 12, wherein the pattern is formed from EL lighting material that has been cut to form the pattern.
- 17. (Original) The safety sign of claim 12, wherein the power source includes a battery.
- 18. (Original) The safety sign of claim 12, wherein the EL lighting surface is yellow when illuminated.
- (Original) The safety sign of claim 12, further including a translucent layer of material 19. over the EL lighting surface, wherein the translucent layer alters a color of the EL lighting surface.
- 20. (Original) The safety sign of claim 12, wherein the EL lighting surface is rectangular and approximately 72 inches wide by 8.5 inches tall.
- 21. (Currently Amended) The safety sign of claim 12, further comprising a mudflap mud flap, wherein the safety sign is attached to the mudflap mud flap.
- 22. (Currently Amended) A mudflap mud flap comprising an EL lighting surface, wherein the EL lighting surface includes a visual safety message.
- 23. (Currently Amended) A vehicle comprising the mudflap mud flap of claim 22.